

This PDF is generated from: <https://marmotresceramics.es/Fri-08-Sep-2017-8321.html>

Title: Structural design of flat single-axis photovoltaic support

Generated on: 2026-04-17 00:10:36

Copyright (C) 2026 MARMOTTES SOLAR. All rights reserved.

For the latest updates and more information, visit our website: <https://marmotresceramics.es>

What are the design variables of a single-axis photovoltaic plant?

This paper presents an optimisation methodology that takes into account the most important design variables of single-axis photovoltaic plants, including irregular land shape, size and configuration of the mounting system, row spacing, and operating periods (for backtracking mode, limited range of motion, and normal tracking mode).

What are the dynamic characteristics of photovoltaic support systems?

Key findings are as follows. Dynamic characteristics of tracking photovoltaic support systems obtained through field modal testing at various inclinations, revealing three torsional modes within the 2.9-5.0 Hz frequency range, accompanied by relatively small modal damping ratios ranging from 1.07 % to 2.99 %.

What are the dynamic characteristics of the tracking photovoltaic support system?

Through processing and analyzing the measured modal data of the tracking photovoltaic support system with Donghua software, the dynamic characteristic parameters of the tracking photovoltaic support system could be obtained, including frequencies, vibration modes and damping ratio.

Which mounting system configuration is best for commercial photovoltaic plants?

The mounting system configuration used in the optimal layout is the one with the best levelised cost of energy efficiency, 1.09. The presented optimisation methodology can be utilised to facilitate the optimal design of commercial photovoltaic plants with single-axis trackers.

This paper presents an optimisation methodology that takes into account the most important design variables of single-axis photovoltaic plants, including irregular land shape, size and configuration of ...

Wind-induced vibration in photovoltaic tracking support can lead to structural instability and even component fractures under extreme conditions. Considering the effects of fluid forces and ...

Figure 2 - Design B: Adjustable support structure design (IRIS - PTOLEMEO) Load calculation Wind direction is stochastic and therefore it is necessary to compute the pressure ...

What are the design variables of a single-axis photovoltaic plant? This paper presents an optimisation

Structural design of flat single-axis photovoltaic support

methodology that takes into account the most important design variables of single-axis photovoltaic ...

The mounting system configuration used in the optimal layout is the one with the best levelised cost of energy efficiency, 1.09. The presented optimisation methodology can be utilised to ...

Lorenzo et al. (2002) designed the tracking of photovoltaic systems with a single vertical axis. The vertical single axis tracking also called as azimuth tracking is mainly used for the energy gain which ...

Abundant solar resources and increasing electricity demand make solar energy a promising renewable energy source in Sub-Saharan Africa. However, conventional stationary ...

Modal parameters and conclusions of the solar tracking photovoltaic support system serving as a reference for wind resistance analysis. The tracking photovoltaic support system is a ...

2?Flexible on-site adjustment:With industry-leading terrain adjustment design, it can achieve adjustments in all directions, simplify installation, and maximize photovoltaic power generation.

The invention relates to a single-axis follower support system (1) for a solar collector (9) comprising a stationary structure (2) for anchoring to the ground; and a platform (30) ...

Web: <https://marmotresceramics.es>

